

# IGEL UD9

## THE ALL-IN-ONE FOR THE HIGH-PERFORMANCE WORKER

Integrated into a 21.5" widescreen display, the UD9 provides numerous interfaces and integrated features such as touchscreen, WLAN or a smartcard reader. The compact all-in-one thin client supports a wide range of applications and due to its quad-core processor it allows high-performance access to all major central computing infrastructures.

- **21.5" LCD monitor (55 cm)**  
Increased user comfort and productivity
- **All-in-One Thin Client**  
Display with integrated thin client, small footprint, and optimized design
- **Touchscreen display (optional)**  
Use without keyboard and mouse, e.g., as a kiosk or PoS
- **Integrated WLAN module (optional)**  
Use of the latest wireless standard enables optimal connectivity even without wired network infrastructure
- **Integrated smartcard reader (optional)**  
Excellent for highly secure two-factor authentication, shared desktops or roaming users

### ALL INCLUSIVE



Management Software



All Updates



Technical Support



Extended Warranty



<b>SYSTEM</b>	
Available Operating Systems	IGEL Linux 10
Management	IGEL Universal Management Suite (included)
Processor	Intel Celeron J1900 1.99 – 2.42 GHz (Quad-Core)
Chipset	Intel Bay Trail SoC
<b>MEMORY</b>	
RAM (DDR3L)	2 GB
Flash Memory	4 GB, larger SSD modules on request
<b>GRAPHICS</b>	
Chipset	Intel HD Graphics
Video Memory	128 - 512MB Shared Memory
Ports (supported resolutions)	1x DisplayPort 1.2a (2560 x 1600) Dualview: Intern (FullHD) 1920 x 1080
<b>NETWORK</b>	
Ethernet	10/100/1000 Base-T
WLAN	optional, 802.11 a/b/g/n
<b>AUDIO</b>	
Chipset	Realtek High Definition Audio (ALC269)
Ports	1x Line-out
Speakers	2x back
<b>PERIPHERAL INTERFACES</b>	
PS/2	1x
Serial	1x
USB 2.0	4x
USB 3.0	2x
Security Lock	1x back
<b>DISPLAY</b>	
Size	21.5
Aspect Ratio	16:9
Brightness	250 cd/m <sup>2</sup>
Contrast Ratio	1000:1
Viewing Angle	178/170
Response time	1.5 ms
<b>DIMENSIONS</b>	
Device (H x D x W), upright	327 x 514 x 264 mm with foot, 100 x 514 x 330 mm without foot
Packaging (H x D x W), horizontal	465 x 650 x 335 mm
Weight (incl. foot)	8.12kg (UD9); 9.26kg (UD9 Touch)
<b>ENVIRONMENT</b>	
Cooling	Fanless convection
Operating Temperature	0° to 40°C
Operating Humidity	30% - 90%, non-condensing
<b>POWER</b>	
Input	Auto sensing 100 - 240 VAC / 50/60 Hz
Power Supply	External
Power Consumption: Idle   Sleep	26W / <3W
<b>OPTIONS</b>	
Integrated Smartcard Reader	For secure smartcard-based authentication
Integrated WLAN Module	For environments with no physical network infrastructure
Touchscreen Display	For public facing or space-constraint environments
USB-to-Serial Adapter	For connecting peripherals that require a serial port
USB-to-Parallel Adapter	For connecting printers that require a parallel port
DisplayPort-DVI-Adapter	For connecting a monitor that requires a DVI port
Shared WorkPlace	It allows user-dependent configuration based on setting profiles
Multimedia Codec Pack	Required for multimedia re-direction and full multimedia functionality
<b>ZERTIFIKATE/PRÜFZEICHEN</b>	
CE, TÜV-GS, cULus, FCC Class B, ICES-003, RCM, VCCI, BSMI, CCC, WEEE, RoHS, China RoHS, Energy Star	For questions about product compliance or certification, please contact <a href="mailto:regulatory.compliance@igel.com">regulatory.compliance@igel.com</a> .