

Model CD7012/7014

ClearCube Cloud Desktop Firmware is a minimal-footprint option for ClearCube CD7012/7014 ZERO+ clients. The Cloud Desktop platform minimizes the pains and risks of switching to VDI environments, making it fast and easy for organizations and companies of all sizes to immediately benefit from VDI client computing.



Cloud Desktop Firmware comes with support for PCoIP, VMware Horizon with Blast Extreme, and CITRIX HDX remote connectivity protocols. This firmware enables Administrators to centrally-manage secure and virus-proof CD7012/7014 ZERO+ clients that can connect to hosted desktops, cloud-hosted desktops, or centrally-hosted applications out of the box.

ClearCube Cloud Desktop Management is a browser-based administration tool that helps IT manage, configure, monitor and update CD7012/7014 ZERO+ clients from one place. Features such as network booting to remove all local storage, real-time monitoring & tactical overview, job scheduling and asset management, and peripheral inventory take the burden out of managing devices on your network.

CD7012/7014 ZERO+ Client Specifications

Processor	AMD GX-215JJ SoC: 1.5-2.0 GHz dual-core with Radeon R2E based graphics core (2CU)
Memory	4GB DDR4 SO-DIMM single-channel SDRAM, non-ECC
Display	3840 x 1080 UHD at 60 Hz, static screen (x1) 2560x1600 at 60HZ, static screen (x1) 1920 x 1200 FHD at 60 Hz (60 fps), video playback (x2)
Storage	4GB solder-on (non-removable) eMMC
I/O Physical	Dual-mode DisplayPort x 2 USB 3.0 x 4 USB 2.0 x 2 3.5mm audio out jack (front) 3.5mm audio in jack (front) 1W internal speaker x 1
Wireless (Optional)	2.4G and 5G dual-band 802.11 a/b/g/n/ac Wi-Fi (2T/2R) Bluetooth HS + 4.1 BLE integrated wireless with external dual antennas
Networking	Fiber SFP Module 1000BASE-SX or LX, LC connector or 1000 Base-T WLAN x 1 (optional, Wi-Fi 2.4G and 5G, Bluetooth 3.0 and 4.1)
Temperature	Operation: 32 to 104 °F (0 to 40 °C) Storage: -4 to 140 °F (-20 to 70 °C)
Relative Humidity	Relative (non-condensing): 10% to 90% Storage: 5% to 95%
Power	24W, DC 12V/2A external power adapter
Mounting	VESA bracket (optional) Optical drive/DVD writer (optional)
Security	Kensington Slot for use with Kensington locks Integrated PKI approved smart card reader on CD7014 Model
Physical Characteristics	Metal
Dimension	6.5inches x (H) x 1.5 inches (W) x 5 inches (D)
Regulatory Compliance	CE/FCC

9 W I X L I J S P R S Q T U V W X

Model CD Zero 2 NCM Web Ordering Information

Model No.	Part Number	Part Description
CD	G0900	CD Zero 2 N W U
%)	% & < G T Q 2 N W U
' E P P	-	
) Q E M P W E P I W \$ G P I E V G Y F I G S Q		
X S S V H I V S V J S V Q S V I M R J S V Q E X M S R		