

CALMO XS



Power Saving



Terminalblock
DC-In



Hardware
Watchdog

Specifications

OS	<ul style="list-style-type: none"> • Windows 10/11 Pro / IoT • IGEL Ready (OS11) • Linux 64-bit
CPU	<ul style="list-style-type: none"> • Intel® Celeron J4005, 2x 2,7 GHz • Intel® Celeron J4105, 4x 2,5GHz • Intel® Pentium Silver J5005, 4x 2,8GHz
RAM	1x SO-DIMM DDR4 PC2400, max. 16 GB
Storage	1x M.2 B-Key 2242/2260/2280 SATA
Graphics	Intel® UHD 600/605
Display Interface 1	DisplayPort 1.2 (4096 x 2304 @ 60Hz)
Display Interface 2	DisplayPort 1.2 (4096 x 2304 @ 60Hz)
Audio	Realtek ALC671 – 7.1 HD Audio
LAN	2x RJ45 @ 10/100/1000 Mbit/s (Intel® i210 + Realtek RTL8111G)
Power supply	DC-Input: 8-24V

Interfaces

Front	<ul style="list-style-type: none"> • 2x USB 3.1 Gen1 • Audio
Rear	<ul style="list-style-type: none"> • 4x USB 2.0 • 2x DisplayPort • 2x LAN • 1x RS-232/485/422 1x COM 4-Wire • DC-in Terminalblock
Internal	<ul style="list-style-type: none"> • 1x M.2 2230 • 8-bit GPIO

Additional data

Dimensions	148 x 57 x 157 mm
Weight	approx. 2 kg
IP-Protection	IP50
Temperature	-30 °C up to 60 °C
Special features	<ul style="list-style-type: none"> • Always-On • Wake-on-LAN • PXE-Boot • TPM 2.0 • Watchdog • System Guard • Recovery-BIOS • Kensington Lock
Optional extensions	• WiFi v6 inkl. Bluetooth 5.0
Warranty	2 Years Bring-In (optional up to 5 Years)
Image stability	Available until 2024

Optional Accessories

Mounting	<ul style="list-style-type: none"> • VESA-Mount 100x100 • DIN Rail Mount
-----------------	--

For further information we invite you to visit www.calmo-pc.de

