

OMNIKEY® 6121

Mobile USB Reader

Mobile USB Reader



The portable OMNIKEY® 6121 is designed for SIM-sized smart cards. Carry the reader with your credentials in your pocket or on your key ring and plug it into your PC via the USB port to access your sensitive data. The reader is based on the same technology and drivers as the OMNIKEY® desktop product family and is therefore just as easy to integrate into your application.

The OMNIKEY® 6121 is designed to meet all major standards like ISO 7816, USB CCID, PC / SC, HBCI (Home Banking Computer Interface) and many more.

Usage within an application is based on standardized interfaces like PC / SC. The USB CCID support makes integration into an existing system simple by connecting host and smart card reader without needing additional drivers.

FEATURES:

- Meets major standards, including ISO 7816, USB CCID, PC / SC and HBCI (Home Banking Computer Interface)
- All major operating systems supported
- Supports high-speed data transmission
- UPC barcode for easier logistics
- USB CCID support makes integration into an existing system the easiest ever by connecting host and smart card reader without the need for additional drivers



KEY BENEFITS

- **Easy to install** – Eliminates the need to install drivers; uses native supported CCID drivers within the operating system.
- **Convenient and Reliable** – Elegant design and keychain loop
- **Suits Any Application** – Compatible with virtually any smart card and major PC operating system

OMNIKEY® 6121

Mobile USB Reader



	SMART CARD INTERFACE
Based Model Number	OMNIKEY® 6121
Card Size	ID-000 (SIM size)
Standards	ISO 7816
Supported Card Types	Class A: 5V @ 60 mA; Class B: 3 V @ 60 mA; Class C: 1.8V @35 mA ATR response time up to 1.6 s
Protocols	Asynchronous: T=0; T=1 Synchronous: S=8 (I²C) ; S=9 (3-wire); S=10 (2-wire)
Insertion Cycles	30,000
Smart Card Clock Frequency	Up to 12 MHz
Smart Card detection	Movement detection with auto power-off; Automatic detection of smart card type; Short circuit and thermal protection
8-Pin Handling	C4 / C8 supported
	HOST INTERFACE
USB Interface	USB 2.0 Full Speed Device (12 MBps) USB 3.0 extended operability, tested with hubs/controllers
Operating Systems	Windows 11/10/8.1/8/7/Vista/Server 2012/Server 2008R2 Windows CE (6/7) depending on hardware Linux Debian 6.0+ / Ubuntu 11.04+ / Fedora 15+; Open SUSE 11.4+ Mac OS X; Android™
Driver	CCID native driver from operating system
Supported APIs	PC/SC - API
	HUMAN INTERFACE
Status indicator	Orange LED
	HOUSING
Housing	Grey blue polycarbonate
Dimensions	2.91" x 0.83" x 0.4" (74 x 21 x 10 mm)
Weight	0.35 oz (10g)
	OPERATING CONDITIONS
Operating Temperature	32-131 F (0-55°C)
Operating Humidity	10-90% rH
Storage Temperature	-4 - 176 F (-20 - 80°C)
Meantime Between Failure (MTBF)	500,000 hours
	COMPLIANCE AND REGULATORY
Compliance / Certification	USB 2.0
Regional certifications	CE, UKCA, FCC, UL, VCCI, KCC, MIC, RCM (C-Tick)
Environmental	WEEE, RoHS, Reach
	OPERATING CONDITIONS
Warranty	Two-year manufacturer's warranty



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108

For more global phone numbers click here

© 2025 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2025-03-17-idt-omnikey-6121-mobile-usb-reader-ds-en PLT-00390

Part of ASSA ABLOY